1 Notations

- The symbol const for `const`.
- The symbol ↶ for *function returned value*.
- Template class parameters lead by outlined character. For example: $\mathbb{T}$, $\mathbb{K}$ey, $\mathbb{C}$ompare. Interpreted in `template` definition context.
- Template class parameters dropped, thus C sometimes used instead of C⟨$\mathbb{T}$⟩.
- A "See example" note by ☞. Example output by 🖷.

2 Containers

2.1 Pair

#include <utility>

```
template⟨class T1, class T2⟩
struct pair {
    T1 first;   T2 second;
    pair() {}
    pair(const T1& a, const T2& b):
        first(a), second(b) {}   };
```

2.1.1 Types

pair::**first_type**
pair::**second_type**

2.1.2 Functions & operators

See also 2.2.3.

pair⟨T1,T2⟩
make_pair(const T1&, const T2&);

2.2 Containers — Common

Here X is any of
{**vector**, **deque**, **list**,
set, **multiset**, **map**, **multimap**}

2.2.1 Types

X::**value_type**
X::**reference**
X::**const_reference**
X::**iterator**
X::**const_iterator**
X::**reverse_iterator**
X::**const_reverse_iterator**
X::**difference_type**
X::**size_type**

Iterators reference value_type (See 6).

2.2.2 Members & Operators

X::X();
X::X(const X&);
X::~X();
X& X::**operator=**(const X&);

X::iterator	X::**begin**();	
X::const_iterator	X::**begin**()	const;
X::iterator	X::**end**();	
X::const_iterator	X::**end**()	const;
X::reverse_iterator	X::**rbegin**();	
X::const_reverse_iterator	X::**rbegin**()	const;
X::reverse_iterator	X::**rend**();	
X::const_reverse_iterator	X::**rend**()	const;
X::size_type	X::**size**()	const;
X::size_type	X::**max_size**()	const;
bool	X::**empty**()	const;
void	X::**swap**(X& x);	

void X::**clear**();

2.2.3 Comparison operators

Let, X *v*, *w*. X may also be **pair** (2.1).

v == *w* *v* != *w*
v < *w* *v* > *w*
v <= *w* *v* >= *w*

All done lexicographically and ↶bool.

2.3 Sequence Containers

S is any of {**vector**, **deque**, **list**}

2.3.1 Constructors

S::S(S::size_type *n*,
const S::value_type& *t*);
S::S(S::const_iterator *first*,
S::const_iterator *last*); ☞*7.2, 7.3*

2.3.2 Members

S::iterator // *inserted copy*
S::**insert**(S::iterator *before*,
const S::value_type& *val*);

S::iterator // *inserted copy*
S::**insert**(S::iterator *before*,
S::size_type *nVal*,
const S::value_type& *val*);

S::iterator // *inserted copy*
S::**insert**(S::iterator *before*,
S::const_iterator *first*,
S::const_iterator *last*);

S:iterator S::**erase**(S::iterator *position*);

S:iterator S::**erase**(S::const_iterator *first*,
↶*post erased* S::const_iterator *last*);

void S::**push_back**(const S::value_type& *x*);

void S::**pop_back**();

S::reference S::**front**();

S::const_reference S::**front**() const;

S::reference S::**back**();

S::const_reference S::**back**() const;

2.4 Vector

#include <vector>

```
template⟨class T,
          class Alloc=allocator⟩
class vector;
```

See also 2.2 and 2.3.

size_type vector::**capacity**() const;

void vector::**reserve**(size_type *n*);

vector::reference
vector::**operator[]**(size_type *i*);

vector::const_reference
vector::**operator[]**(size_type *i*) const;

☞ 7.1.

2.5 Deque

#include <deque>

```
template⟨class 𝕋,
          class 𝔸lloc=allocator⟩
class deque;
```

Has all of **vector** functionality (see 2.4).

void deque::**push_front**(const 𝕋& *x*);

void deque::**pop_front**();

2.6 List

#include <list>

```
template⟨class 𝕋,
          class 𝔸lloc=allocator⟩
class list;
```

See also 2.2 and 2.3.

void list::**pop_front**();

void list::**push_front**(const 𝕋& *x*);

void // *move all x (&x ≠ this) before pos*
list::**splice**(iterator *pos*, list⟨𝕋⟩& *x*); ☞7.2

void // *move x's xElemPos before pos*
list::**splice** (iterator *pos*,
list⟨𝕋⟩& *x*,
iterator *xElemPos*); ☞7.2

void // *move x's [xFirst,xLast) before pos*
list::**splice** (iterator *pos*,
list⟨𝕋⟩& *x*,
iterator *xFirst*,
iterator *xLast*); ☞7.2

void list::**remove**(const 𝕋& *value*);

void list::**remove_if**(ℙredicate *pred*);

// *after call:* ∀ this iterator $p, *p \neq *(p+1)$
void list::**unique**(𝔹inaryPredicate *binPred*);

void // *as before but,* $\neg binPred(*p, *(p+1))$
list::**unique**(𝔹inaryPredicate *binPred*);

// *Assuming both* this *and x sorted*
void list::**merge**(list⟨𝕋⟩& *x*);

// *merge and assume sorted by cmp*
void list::**merge**(list⟨𝕋⟩& *x*, ℂompare *cmp*);

void list::**reverse**();

void list::**sort**();

void list::**sort**(ℂompare *cmp*);

2.7 Sorted Associative

Here A any of
{**set**, **multiset**, **map**, **multimap**}.

2.7.1 Types

For A=[multi]set, columns are the same

A::**key_type**	A::**value_type**
A::**key_compare**	A::**value_compare**

2.7.2 Constructors

A::A(ℂompare *c*=ℂompare())

A::A(A::const_iterator *first*,
A::const_iterator *last*,
ℂompare *c*=ℂompare());

2.7.3 Members

A::key_compare A::**key_comp**() const;
A::value_compare A::**value_comp**() const;

A::iterator
A::**insert**(A::iterator *hint*,
const A::value_type& *val*);

void A::**insert**(A::iterator *first*,
A::iterator *last*);

A::size_type // *# erased*
A::**erase**(const A::key_type& *k*);
void A::**erase**(A::iterator *p*);
void A::**erase**(A::iterator *first*,
A::iterator *last*);

A::size_type
A::**count**(const A::key_type& *k*) const;

A::iterator A::**find**(const A::key_type& *k*) const;

A::iterator
A::**lower_bound**(const A::key_type& *k*) const;

A::iterator
A::**upper_bound**(const A::key_type& *k*) const;

pair⟨A::iterator, A::iterator⟩ // see 4.3.1
A::**equal_range**(const A::key_type& *k*) const;

2.8 Set

#include <set>

```
template⟨class 𝕂ey,
          class ℂompare=less⟨𝕂ey⟩,
          class 𝔸lloc=allocator⟩
class set;
```

See also 2.2 and 2.7.

set::**set**(const ℂompare& *cmp*=ℂompare());

pair⟨set::iterator, bool⟩ // `bool` = *if new*
set::**insert**(const set::value_type& *x*);

2.9 Multiset

#include <multiset.h>

```
template⟨class 𝕂ey,
          class ℂompare=less⟨𝕂ey⟩,
          class 𝔸lloc=allocator⟩
class multiset;
```

See also 2.2 and 2.7.

multiset::**multiset**(
const ℂompare& *cmp*=ℂompare());

multiset::**multiset**(
𝕀nputIterator *first*,
𝕀nputIterator *last*,
const ℂompare& *cmp*=ℂompare());

multiset::iterator // *inserted copy*
multiset::**insert**(const multiset::value_type& *x*);

2.10 Map

#include <map>

```
template⟨class 𝕂ey, class 𝕋,
          class ℂompare=less⟨𝕂ey⟩,
          class 𝔸lloc=allocator⟩
class map;
```

See also 2.2 and 2.7.

2.10.1 Types

map::**value_type** // pair⟨const 𝕂ey,𝕋⟩

2.10.2 Members

map::**map**(
const Compare& *cmp*=Compare());

pair⟨map::iterator, bool⟩ // `bool` = *if new*
map::**insert**(const map::value_type& *x*);

T& map:**operator**[](const map::key_type&);

map::const_iterator
map::**lower_bound**(
const map::key_type& *k*) const;

map::const_iterator
map::**upper_bound**(
const map::key_type& *k*) const;

pair⟨map::const_iterator, map::const_iterator⟩
map::**equal_range**(

const map::key_type& *k*) const;

Example

```
typedef map<string, int> MSI;
MSI  nam2num;
nam2num.insert(MSI::value_type("one", 1));
nam2num.insert(MSI::value_type("two", 2));
nam2num.insert(MSI::value_type("three", 3));
int n3 = nam2num["one"] + nam2num["two"];
cout << n3 << " called ";
for (MSI::const_iterator i = nam2num.begin();
     i != nam2num.end();   ++i)
  if ((*i).second == n3)
    {cout << (*i).first << endl;}
```

```
3 called three
```

2.11 Multimap

#include <multimap.h>

```
template⟨class Key, class T,
          class Compare=less⟨Key⟩,
          class Alloc=allocator⟩
class multimap;
```

See also 2.2 and 2.7.

2.11.1 Types

multimap::**value_type** // pair⟨const Key,T⟩

2.11.2 Members

multimap::**multimap**(
const Compare& *cmp*=Compare());

multimap::**multimap**(
InputIterator *first*,
InputIterator *last*,
const Compare& *cmp*=Compare());

multimap::const_iterator
multimap::**lower_bound**(
const multimap::key_type& *k*) const;

multimap::const_iterator
multimap::**upper_bound**(
const multimap::key_type& *k*) const;

pair⟨multimap::const_iterator,
multimap::const_iterator⟩
multimap::**equal_range**(
const multimap::key_type& *k*) const;

3 Container Adaptors

3.1 Stack Adaptor

#include <stack>

```
template⟨class T,
          class Container=deque⟨T⟩ ⟩
class stack;
```

Default constructor. Container must have `back()`, `push_back()`, `pop_back()`. So **vector**, **list** and **deque** can be used.

bool stack::**empty**() const;

Container::size_type stack::**size**() const;

void
stack::**push**(const Container::value_type& x);

void stack::**pop**();

const Container::value_type&
stack::**top**() const;

void Container::value_type& stack::**top**();

Comparision Operators

bool **operator==**(const stack& *s0*,
const stack& *s1*);

bool **operator<**(const stack& *s0*,
const stack& *s1*);

3.2 Queue Adaptor

#include <queue>

```
template⟨class T,
          class Container=deque⟨T⟩ ⟩
class queue;
```

Default constructor. Container must have `empty()`, `size()`, `back()`, `front()`, `push_back()` and `pop_front()`. So **list** and **deque** can be used.

bool queue::**empty**() const;

Container::size_type queue::**size**() const;

void
queue::**push**(const Container::value_type& x);

void queue::**pop**();

const Container::value_type&
queue::**front**() const;

Container::value_type& queue::**front**();

const Container::value_type&
queue::**back**() const;

Container::value_type& queue::**back**();

Comparision Operators

bool **operator==**(const queue& *q0*,
const queue& *q1*);

bool **operator<**(const queue& *q0*,
const queue& *q1*);

3.3 Priority Queue

#include <queue>

```
template⟨class T,
          class Container=vector⟨T⟩,
          class Compare=less⟨T⟩ ⟩
class priority_queue;
```

Container must provide random access iterator and have `empty()`, `size()`, `front()`, `push_back()` and `pop_back()`. So **vector** and **deque** can be used.

Mostly implemented as *heap*.

3.3.1 Constructors

explicit **priority_queue::priority_queue**(
const ℂompare& comp=ℂompare());
priority_queue::priority_queue(
𝕀nputIterator *first*,
𝕀nputIterator *last*,
const ℂompare& *comp*=ℂompare());

3.3.2 Members

bool priority_queue::**empty**() const;

ℂontainer::size_type
priority_queue::**size**() const;

const ℂontainer::value_type&
priority_queue::**top**() const;

ℂontainer::value_type& priority_queue::**top**();

void priority_queue::**push**(
const ℂontainer::value_type& x);
void priority_queue::**pop**();

No comparision operators.

4 Algorithms

#include <algorithm>

STL algorithms use iterator type parameters. Their *names* suggest their category (See 6.1).
For abbreviation, the clause —
`template ⟨class 𝔽oo, ...⟩` is dropped. The outlined leading character can suggest the `template` context.
Note: When looking at two sequences: $S_1 = [first_1, last_1)$ and $S_2 = [first_2, ?)$ or $S_2 = [?, last_2)$ — caller is responsible that function will not overflow S_2.

4.1 Query Algorithms

𝔽unction // *f not changing* [*first, last*)
for_each(𝕀nputIterator *first*,
𝕀nputIterator *last*,
𝔽unction *f*); ☞7.4

𝕀nputIterator // *first i so i==last or* `*i==val`
find(𝕀nputIterator *first*,
𝕀nputIterator *last*,
const 𝕋 *val*); ☞7.2

𝕀nputIterator // *first i so i==last or* `pred(i)`
find_if(𝕀nputIterator *first*,
𝕀nputIterator *last*,
ℙredicate *pred*); ☞7.7

𝔽orwardIterator // *first duplicate*
adjacent_find(𝔽orwardIterator *first*,
𝔽orwardIterator *last*);

𝔽orwardIterator // *first binPred-duplicate*
adjacent_find(𝔽orwardIterator *first*,
𝔽orwardIterator *last*,
𝔹inaryPredicate *binPred*);

void // *n = # equal val*
count(𝔽orwardIterator *first*,
𝔽orwardIterator *last*,
const 𝕋 *val*,
𝕊ize& *n*);

void // *n = # satisfying pred*
count_if(𝔽orwardIterator *first*,
𝔽orwardIterator *last*,
ℙredicate *pred*,
𝕊ize& *n*);

// ↶ *bi-pointing to first* !=
pair⟨𝕀nputIterator1, 𝕀nputIterator2⟩
mismatch(𝕀nputIterator1 *first1*,
𝕀nputIterator1 *last1*,
𝕀nputIterator2 *first2*);

// ↶ *bi-pointing to first binPred-mismatch*
pair⟨𝕀nputIterator1, 𝕀nputIterator2⟩
mismatch(𝕀nputIterator1 *first1*,
𝕀nputIterator1 *last1*,
𝕀nputIterator2 *first2*,
𝔹inaryPredicate *binPred*);

bool
equal(𝕀nputIterator1 *first1*,
𝕀nputIterator1 *last1*,
𝕀nputIterator2 *first2*);

bool
equal(𝕀nputIterator1 *first1*,
𝕀nputIterator1 *last1*,
𝕀nputIterator2 *first2*,
𝔹inaryPredicate *binPred*);

// $[first_2, last_2) \sqsubseteq [first_1, last_1)$
𝔽orwardIterator1
search(𝔽orwardIterator1 *first1*,
𝔽orwardIterator1 *last1*,
𝔽orwardIterator2 *first2*,
𝔽orwardIterator2 *last2*);

// $[first_2, last_2) \sqsubseteq_{binPred} [first_1, last_1)$
𝔽orwardIterator1
search(𝔽orwardIterator1 *first1*,
𝔽orwardIterator1 *last1*,
𝔽orwardIterator2 *first2*,
𝔽orwardIterator2 *last2*,
𝔹inaryPredicate *binPred*);

4.2 Mutating Algorithms

𝕆utputIterator // ↶ $first_2 + (last_1 - first_1)$
copy(𝕀nputIterator *first1*,
𝕀nputIterator *last1*,
𝕆utputIterator *first2*);

// ↶ $last_2 - (last_1 - first_1)$
𝔹idirectionalIterator2
copy_backward(
𝔹idirectionalIterator1 *first1*,
𝔹idirectionalIterator1 *last1*,
𝔹idirectionalIterator2 *last2*);

void **swap**(𝕋& x, 𝕋& y);

𝔽orwardIterator2 // ↶ $first_2 + \#[first_1, last_1)$
swap_ranges(𝔽orwardIterator1 *first1*,
𝔽orwardIterator1 *last1*,
𝔽orwardIterator2 *first2*);

𝕆utputIterator // ↶ $result + (last_1 - first_1)$
transform(𝕀nputIterator *first*,
𝕀nputIterator *last*,
𝕆utputIterator *result*,
𝕌naryOperation *op*); ☞7.6

𝕆utputIterator // $\forall s_i^k \in S_k \;\; r_i = bop(s_i^1, s_i^2)$
transform(𝕀nputIterator1 *first1*,
𝕀nputIterator1 *last1*,
𝕀nputIterator2 *first2*,
𝕆utputIterator *result*,
𝔹inaryOperation *bop*);

void **replace**(ForwardIterator *first*,
ForwardIterator *last*,
const T& *oldVal*,
const T& *newVal*);

void
replace_if(ForwardIterator *first*,
ForwardIterator *last*,
Predicate& *pred*,
const T& *newVal*);

OutputIterator // $\curvearrowleft$ $result_2 + \#[first, last)$
replace_copy(InputIterator *first*,
InputIterator *last*,
OutputIterator *result*,
const T& *oldVal*,
const T& *newVal*);

OutputIterator // *as above but using pred*
replace_copy_if(InputIterator *first*,
InputIterator *last*,
OutputIterator *result*,
Predicate& *pred*,
const T& *newVal*);

void **fill**(ForwardIterator *first*,
ForwardIterator *last*,
const T& *value*);

void **fill_n**(ForwardIterator *first*,
Size *n*,
const T& *value*);

void // *by calling gen*()
generate(ForwardIterator *first*,
ForwardIterator *last*,
Generator *gen*);

void // *n calls to gen*()
generate_n(ForwardIterator *first*,
Size *n*,
Generator *gen*);

All variants of **remove** and **unique** return iterator to *new end* or *past last copied*.

ForwardIterator // *[*$\curvearrowleft$*,last) is all value*
remove(ForwardIterator *first*,
ForwardIterator *last*,
const T& *value*);

ForwardIterator // *as above but using pred*
remove_if(ForwardIterator *first*,
ForwardIterator *last*,
Predicate *pred*);

OutputIterator // $\curvearrowleft$ *past last copied*
remove_copy(InputIterator *first*,
InputIterator *last*,
OutputIterator *result*,
const T& *value*);

OutputIterator // *as above but using pred*
remove_copy_if(InputIterator *first*,
InputIterator *last*,
OutputIterator *result*,
Predicate *pred*);

All variants of **unique** template functions remove *consecutive* (*binPred*-) duplicates. Thus usefull after sort (See 4.3).

ForwardIterator // *[*$\curvearrowleft$*,last) gets repetitions*
unique(ForwardIterator *first*,
ForwardIterator *last*);

ForwardIterator // *as above but using binPred*
unique(ForwardIterator *first*,
ForwardIterator *last*,
BinaryPredicate *binPred*);

OutputIterator // $\curvearrowleft$ *past last copied*
unique_copy(InputIterator *first*,
InputIterator *last*,
OutputIterator *result*,
const T& *result*);

OutputIterator // *as above but using binPred*
unique_copy(InputIterator *first*,
InputIterator *last*,
OutputIterator *result*,
BinaryPredicate *binPred*);

void
reverse(BidirectionalIterator *first*,
BidirectionalIterator *last*);

OutputIterator // $\curvearrowleft$ *past last copied*
reverse_copy(BidirectionalIterator *first*,
BidirectionalIterator *last*,
OutputIterator *result*);

void // *with first moved to middle*
rotate(ForwardIterator *first*,
ForwardIterator *middle*,
ForwardIterator *last*);

OutputIterator // *first to middle* position
rotate_copy(ForwardIterator *first*,
ForwardIterator *middle*,
ForwardIterator *last*,
OutputIterator *result*);

void
random_shuffle(
RandomAccessIterator *first*,
RandomAccessIterator *result*);

void // *rand*() *returns* `double` *in* $[0, 1)$
random_shuffle(
RandomAccessIterator *first*,
RandomAccessIterator *last*,
RandomGenerator *rand*);

BidirectionalIterator // *begin with* `true`
partition(BidirectionalIterator *first*,
BidirectionalIterator *last*,
Predicate *pred*);

BidirectionalIterator // *begin with* `true`
stable_partition(
BidirectionalIterator *first*,
BidirectionalIterator *last*,
Predicate *pred*);

4.3 Sort and Application

void **sort**(RandomAccessIterator *first*,
RandomAccessIterator *last*);

void **sort**(RandomAccessIterator *first*,
RandomAccessIterator *last*,
☞7.3 Compare *comp*);

void
stable_sort(RandomAccessIterator *first*,
RandomAccessIterator *last*);

void
stable_sort(RandomAccessIterator *first*,
RandomAccessIterator *last*,
Compare *comp*);

void // *[first,middle) sorted,*
partial_sort(// *[middle,last) eq-greater*
RandomAccessIterator *first*,
RandomAccessIterator *middle*,
RandomAccessIterator *last*);

void // *as above but using* $comp(e_i, e_j)$
partial_sort(
RandomAccessIterator *first*,
RandomAccessIterator *middle*,
RandomAccessIterator *last*,
Compare *comp*);

RandomAccessIterator // *post last sorted*
partial_sort_copy(
InputIterator *first*,
InputIterator *last*,
RandomAccessIterator *resultFirst*,
RandomAccessIterator *resultLast*);

RandomAccessIterator
partial_sort_copy(
InputIterator *first*,
InputIterator *last*,
RandomAccessIterator *resultFirst*,
RandomAccessIterator *resultLast*,
Compare *comp*);

Let $n = position - first$, **nth_element** partitions $[first, last)$ into: $L = [first, position)$, e_n, $R = [position + 1, last)$ such that $\forall l \in L, \forall r \in R \quad l \not> e_n \leq r$.

void
nth_element(
RandomAccessIterator *first*,
RandomAccessIterator *position*,
RandomAccessIterator *last*);

void // *as above but using* $comp(e_i, e_j)$
nth_element(
RandomAccessIterator *first*,
RandomAccessIterator *position*,
RandomAccessIterator *last*,
Compare *comp*);

4.3.1 Binary Search

bool
binary_search(ForwardIterator *first*,
ForwardIterator *last*,
const T& *value*);

bool
binary_search(ForwardIterator *first*,
ForwardIterator *last*,
const T& *value*,
Compare *comp*);

ForwardIterator
lower_bound(ForwardIterator *first*,
ForwardIterator *last*,
const T& *value*);

ForwardIterator
lower_bound(ForwardIterator *first*,
ForwardIterator *last*,
const T& *value*,
Compare *comp*);

ForwardIterator
upper_bound(ForwardIterator *first*,
ForwardIterator *last*,
const T& *value*);

ForwardIterator
upper_bound(ForwardIterator *first*,
ForwardIterator *last*,
const T& *value*,
Compare *comp*);

equal_range returns iterators pair that lower_bound and upper_bound return.

pair⟨ForwardIterator,ForwardIterator⟩
equal_range(ForwardIterator *first*,
ForwardIterator *last*,
const T& *value*);

pair⟨ForwardIterator,ForwardIterator⟩
equal_range(ForwardIterator *first*,
ForwardIterator *last*,
const T& *value*,
Compare *comp*);

☞ 7.5

4.3.2 Merge

Assuming $S_1 = [first_1, last_1)$ and $S_2 = [first_2, last_2)$ are sorted, stably merge them into $[result, result + N)$ where $N = |S_1| + |S_2|$.

OutputIterator
merge(InputIterator1 *first1*,
InputIterator1 *last1*,
InputIterator2 *first2*,
InputIterator2 *last2*,
OutputIterator *result*);

OutputIterator
merge(InputIterator1 *first1*,
InputIterator1 *last1*,
InputIterator2 *first2*,
InputIterator2 *last2*,
OutputIterator *result*,
Compare *comp*);

void // *ranges [first,middle) [middle,last)*
inplace_merge(// *into [first,last)*
BidirectionalIterator *first*,
BidirectionalIterator *middle*,
BidirectionalIterator *last*);

void // *as above but using comp*
inplace_merge(
BidirectionalIterator *first*,
BidirectionalIterator *middle*,
BidirectionalIterator *last*,
Compare *comp*);

4.3.3 Functions on Sets

Can work on *sorted associcative* containers (see 2.7). For **multiset** the interpretation of — *union*, *intersection* and *difference* is by: *maximum*, *minimum* and *substraction* of occurrences respectably.

Let $S_i = [first_i, last_i)$ for $i = 1, 2$.

bool // $S_1 \supseteq S_2$
includes(InputIterator1 *first1*,
InputIterator1 *last1*,
InputIterator2 *first2*,
InputIterator2 *last2*);

bool // *as above but using comp*
includes(InputIterator1 *first1*,
InputIterator1 *last1*,
InputIterator2 *first2*,
InputIterator2 *last2*,
Compare *comp*);

OutputIterator // $S_1 \cup S_2$, ↶*past end*
set_union(InputIterator1 *first1*,
InputIterator1 *last1*,
InputIterator2 *first2*,
InputIterator2 *last2*,
OutputIterator *result*);

```
OutputIterator // as above but using comp
set_union(InputIterator1  first1,
          InputIterator1  last1,
          InputIterator2  first2,
          InputIterator2  last2,
          OutputIterator  result,
          Compare         comp);

OutputIterator // S1 ∩ S2, ↶past end
set_intersection(InputIterator1  first1,
                 InputIterator1  last1,
                 InputIterator2  first2,
                 InputIterator2  last2,
                 OutputIterator  result);

OutputIterator // as above but using comp
set_intersection(InputIterator1  first1,
                 InputIterator1  last1,
                 InputIterator2  first2,
                 InputIterator2  last2,
                 OutputIterator  result,
                 Compare         comp);

OutputIterator // S1 \ S2, ↶past end
set_difference(InputIterator1  first1,
               InputIterator1  last1,
               InputIterator2  first2,
               InputIterator2  last2,
               OutputIterator  result);

OutputIterator // as above but using comp
set_difference(InputIterator1  first1,
               InputIterator1  last1,
               InputIterator2  first2,
               InputIterator2  last2,
               OutputIterator  result,
               Compare         comp);

OutputIterator // S1△S2, ↶past end
set_symmetric_difference(
    InputIterator1  first1,
    InputIterator1  last1,
    InputIterator2  first2,
    InputIterator2  last2,
    OutputIterator  result);

OutputIterator // as above but using comp
set_symmetric_difference(
    InputIterator1  first1,
    InputIterator1  last1,
    InputIterator2  first2,
    InputIterator2  last2,
    OutputIterator  result,
    Compare         comp);
```

4.3.4 Heap

```
void // (last − 1) is pushed
push_heap(RandomAccessIterator  first,
          RandomAccessIterator  last);

void // as above but using comp
push_heap(RandomAccessIterator  first,
          RandomAccessIterator  last,
          Compare               comp);

void // first is popped
pop_heap(RandomAccessIterator  first,
         RandomAccessIterator  last);

void // as above but using comp
pop_heap(RandomAccessIterator  first,
         RandomAccessIterator  last,
         Compare               comp);

void // [first,last) arbitrary ordered
make_heap(RandomAccessIterator  first,
          RandomAccessIterator  last);

void // as above but using comp
make_heap(RandomAccessIterator  first,
          RandomAccessIterator  last,
          Compare               comp);

void // sort the [first,last) heap
sort_heap(RandomAccessIterator  first,
          RandomAccessIterator  last);

void // as above but using comp
sort_heap(RandomAccessIterator  first,
          RandomAccessIterator  last,
          Compare               comp);
```

4.3.5 Min and Max

```
const T& min(const T& x0, const T& x1);

const T& min(const T&  x0,
             const T&  x1,
             Compare   comp);

const T& max(const T& x0, const T& x1);

const T& max(const T&  x0,
             const T&  x1,
             Compare   comp);

ForwardIterator
min_element(ForwardIterator  first,
            ForwardIterator  last);

ForwardIterator
min_element(ForwardIterator  first,
            ForwardIterator  last,
            Compare          comp);

ForwardIterator
max_element(ForwardIterator  first,
            ForwardIterator  last);

ForwardIterator
max_element(ForwardIterator  first,
            ForwardIterator  last,
            Compare          comp);
```

4.3.6 Permutations

To get all permutations, start with ascending sequence end with descending.

```
bool // ↶ iff available
next_permutation(
    BidirectionalIterator  first,
    BidirectionalIterator  last);

bool // as above but using comp
next_permutation(
    BidirectionalIterator  first,
    BidirectionalIterator  last,
    Compare                comp);

bool // ↶ iff available
prev_permutation(
    BidirectionalIterator  first,
    BidirectionalIterator  last);

bool // as above but using comp
prev_permutation(
    BidirectionalIterator  first,
    BidirectionalIterator  last,
    Compare                comp);
```

4.3.7 Lexicographic Order

bool **lexicographical_compare**(
    InputIterator1 *first1*,
    InputIterator1 *last1*,
    InputIterator2 *first2*,
    InputIterator2 *last2*);
bool **lexicographical_compare**(
    InputIterator1 *first1*,
    InputIterator1 *last1*,
    InputIterator2 *first2*,
    InputIterator2 *last2*,
    Compare *comp*);

4.4 Computational

#include <numeric>

T // $\sum_{[first,last)}$ ☞7.6
accumulate(InputIterator *first*,
    InputIterator *last*,
    T *initVal*);

T // *as above but using binop*
accumulate(InputIterator *first*,
    InputIterator *last*,
    T *initVal*,
    BinaryOperation *binop*);

T // $\sum_i e_i^1 \times e_i^2$ *for* $e_i^k \in S_k, (k = 1, 2)$
inner_product(InputIterator1 *first1*,
    InputIterator1 *last1*,
    InputIterator2 *first2*,
    T *initVal*);

T // *Similar, using* $\sum^{(sum)}$ *and* $\times_{mult}$
inner_product(InputIterator1 *first1*,
    InputIterator1 *last1*,
    InputIterator2 *first2*,
    T *initVal*,
    BinaryOperation *sum*,
    BinaryOperation *mult*);

OutputIterator // $r_k = \sum_{i=first}^{first+k} e_i$
partial_sum(InputIterator *first*,
    InputIterator *last*,
    OutputIterator *result*);

OutputIterator // *as above but using binop*
partial_sum(
    InputIterator *first*,
    InputIterator *last*,
    OutputIterator *result*,
    BinaryOperation *binop*);

OutputIterator // $r_k = s_k - s_{k-1}$ *for* $k > 0$
adjacent_difference(// $r_0 = s_0$
    InputIterator *first*,
    InputIterator *last*,
    OutputIterator *result*);

OutputIterator // *as above but using binop*
adjacent_difference(
    InputIterator *first*,
    InputIterator *last*,
    OutputIterator *result*,
    BinaryOperation *binop*);

5 Function Objects

#include <**functional**>

```
template⟨class Arg, class Result⟩
struct unary_function {
  typedef Arg argument_type;
  typedef Result result_type;}
```

Derived unary objects:
struct **negate**⟨T⟩;
struct **logical_not**⟨T⟩;
☞ 7.6

```
template⟨class Arg1, class Arg2,
         class Result⟩
struct binary_function {
  typedef Arg1 first_argument_type;
  typedef Arg2 second_argument_type;
  typedef Result result_type;}
```

Following derived template objects accept two operands. Result obvious by the name.

struct **plus**⟨T⟩;
struct **minus**⟨T⟩;
struct **multiplies**⟨T⟩;
struct **divides**⟨T⟩;
struct **modulus**⟨T⟩;
struct **equal_to**⟨T⟩;
struct **not_equal_to**⟨T⟩;
struct **greater**⟨T⟩;
struct **less**⟨T⟩;
struct **greater_equal**⟨T⟩;
struct **less_equal**⟨T⟩;
struct **logical_and**⟨T⟩;
struct **logical_or**⟨T⟩;

5.1 Function Adaptors

5.1.1 Negators

```
template⟨class Predicate⟩
class unary_negate : public
  unary_function⟨Predicate::argument_type,
                 bool⟩;
```

unary_negate::**unary_negate**(
    Predicate *pred*);

bool // *negate pred*
unary_negate::**operator()**(
    Predicate::argument_type x);

unary_negate⟨Predicate⟩
not1(const Predicate *pred*);

```
template⟨class Predicate⟩
class binary_negate : public
  binary_function⟨
    Predicate::first_argument_type,
    Predicate::second_argument_type⟩;
    bool⟩;
```

binary_negate::**binary_negate**(
    Predicate *pred*);

bool // *negate pred*
binary_negate::**operator()**(
    Predicate::first_argument_type x
    Predicate::second_argument_type y);

binary_negate⟨Predicate⟩
not2(const Predicate *pred*);

5.1.2 Binders

```
template⟨class 𝕆peration⟩
class binder1st: public
  unary_function⟨
      𝕆peration::second_argument_type,
      𝕆peration::result_type⟩;
```

binder1st::**binder1st**(
const 𝕆peration& *op*,
const 𝕆peration::first_argument_type *y*);

// argument_type *from* unary_function
𝕆peration::result_type
binder1st::**operator()**(
const binder1st::argument_type *x*);

binder1st⟨𝕆peration⟩
bind1st(const 𝕆peration& *op*, const 𝕋& *x*);

```
template⟨class 𝕆peration⟩
class binder2nd: public
  unary_function⟨
      𝕆peration::first_argument_type,
      𝕆peration::result_type⟩;
```

binder2nd::**binder2nd**(
const 𝕆peration& *op*,
const 𝕆peration::second_argument_type *y*);

// argument_type *from* unary_function
𝕆peration::result_type
binder2nd::**operator()**(
const binder2nd::argument_type *x*);

binder2nd⟨𝕆peration⟩
bind2nd(const 𝕆peration& *op*, const 𝕋& *x*);

☞ 7.7.

5.1.3 Pointers to Functions

```
template⟨class 𝔸rg, class ℝesult⟩
class pointer_to_unary_function :
  public unary_function⟨𝔸rg, ℝesult⟩;
```

pointer_to_unary_function⟨𝔸rg, ℝesult⟩
ptr_fun(ℝesult(*x)(𝔸rg));

```
template<class 𝔸rg1, class 𝔸rg2,
         class ℝesult>
class pointer_to_binary_function :
  public binary_function⟨𝔸rg1, 𝔸rg2,
                         ℝesult⟩;
```

pointer_to_binary_function⟨𝔸rg1, 𝔸rg2,
ℝesult⟩
ptr_fun(ℝesult(*x)(𝔸rg1, 𝔸rg2));

6 Iterators

#include <**iterator**>

6.1 Iterators Categories

Here, we will use:

`X`	iterator type.
`a, b`	iterator values.
`r`	iterator reference (`X& r`).
`t`	a value type `T`.

6.1.1 Input, Output, Forward

```
template⟨class 𝕋, class 𝔻istance⟩
class input_iterator;
```

```
class output_iterator;
```

```
template⟨class 𝕋, class 𝔻istance⟩
class forward_iterator;
```

In table follows requirements check list for **I**nput, **O**utput and **F**orward iterators.

Expression; **Requirements**		**I**	**O**	**F**
`X()` `X u`	might be singular			•
`X(a)`	⇒`X(a) == a`	•		•
	`*a=t` ⇔ `*X(a)=t`		•	
`X u(a)` `X u=a`	⇒ `u == a`	•		•
	`u` copy of `a`		•	
`a==b`	equivalence relation	•		•
`a!=b`	⇔`!(a==b)`	•		•
`r = a`	⇒ `r == a`			•
`*a`	convertible to `T`. `a==b` ⇔ `*a==*b`	•		•
`*a=t`	(for *forward*, if `X` mutable)		•	•
`++r`	result is dereferenceable or *past-the-end*. `&r == &++r`	•	•	•
	convertible to `const X&`	•	•	
	convertible to `X&` `r==s`⇔ `++r==++s`			•
`r++`	convertible to `X&` ⇔{`X x=r;++r;return x;`}	•	•	•
`*++r` `*r++`	convertible to `T`	•	•	•

☞ 7.7.

6.1.2 Bidirectional Iterators

```
template⟨class 𝕋, class 𝔻istance⟩
class bidirectional_iterator;
```

The **forward** requirements and:

`--r` Convertible to const `X&`. If ∃ `r==++s` then `--r` refers same as `s`. `&r==&--r`. `--(++r)==r`. (`--r == --s` ⇒ `r==s`.

`r--` ⇔ {`X x=r; --r; return x;`}.

6.1.3 Random Access Iterator

```
template⟨class 𝕋, class 𝔻istance⟩
class random_access_iterator;
```

The **bidirectional** requirements and (`m,n` iterator's *distance* (integral) value):

`r+=n` ⇔ {`for (m=n; m-->0; ++r); for (m=n; m++<0; --r); return r;`} //but time = $O(1)$.
`a+n` ⇔ `n+a` ⇔ {`X x=a; return a+=n]`}
`r-=n` ⇔ `r += -n`.
`a-n` ⇔ `a+(-n)`.
`b-a` Returns iterator's *distance* value n, such that `a+n == b`.
`a[n]` ⇔ `*(a+n)`.
`a<b` Convertible to `bool`, `<` total ordering.
`a<b` Convertible to `bool`, `>` opposite to `<`.
`a<=b` ⇔ `!(a>b)`.
`a>=b` ⇔ `!(a<b)`.

6.2 Stream Iterators

```
template⟨class T,
          class Distance=ptrdiff_t⟩
class istream_iterator :
      input_iterator⟨T, Distance⟩;
```

// *end of stream* ☞7.4
istream_iterator::**istream_iterator**();

istream_iterator::**istream_iterator**(
istream& *s*); ☞7.4

istream_iterator::**istream_iterator**(
const istream_iterator⟨T, Distance⟩&);

istream_iterator::**~istream_iterator**();

const T& istream_iterator::**operator***() const;

istream_iterator& // *Read and store* T *value*
istream_iterator::**operator++**() const;

bool // *all end-of-streams are equal*
operator==(const istream_iterator,
const istream_iterator);

```
template⟨class T⟩
class ostream_iterator :
      public output_iterator⟨T⟩;
```

// *If delim* ≠ 0 *add after each write*
ostream_iterator::**ostream_iterator**(
ostream& *s*,
const char* *delim=0);*

ostream_iterator::**ostream_iterator**(
const ostream_iterator *s*);

ostream_iterator& // *Assign & write (*o=t)*
ostream_iterator::**operator***() const;

ostream_iterator&
ostream_iterator::**operator=**(
const ostream_iterator *s*);

ostream_iterator& // *No-op*
ostream_iterator::**operator++**();

ostream_iterator& // *No-op*
ostream_iterator::**operator++**(int);

☞ 7.4.

6.3 Adaptors Iterators

6.3.1 Reverse Iterators

Transform $[i \nearrow j) \mapsto [j-1 \searrow i-1)$.

```
template⟨class BidirectionalIterator,
          class T, class Reference= &T,
          class Distance = ptrdiff_t⟩
class
 reverse_bidirectional_iterator :
  public
   bidirectional_iterator⟨T, Distance⟩;
```

```
template⟨class RandomAccessIterator,
          class T, class Reference= &T,
          class Distance = ptrdiff_t⟩
class
 reverse_iterator :
  public
   random_access_iterator⟨T, Distance⟩;
```

Denote
RI = **reverse_bidirectional_iterator**,
AI = BidirectionalIterator,
or
RI = **reverse_iterator**
AI = RandomAccessIterator.

Abbreviate:
typedef RI<AI, T,
Reference, Distance⟩ **self**;

// *Default constructor* ⇒ *singular value*
self::RI();

explicit // *Adaptor Constructor*
self::RI(AI *i*);

AI self::**base**(); // *adpatee's position*

// *so that:* `&*(RI(i)) == &*(i-1)` Reference
self::**operator***();

self // *position to & return* base()-1
RI::**operator++**();

self& // *return old position and move*
RI::**operator++**(int); // *to* base()-1

self // *position to & return* base()+1
RI::**operator--**();

self& // *return old position and move*
RI::**operator--**(int); // *to* base()+1

bool // ⇔ *s0*.base() == *s1*.base()
operator==(const self& *s0*, const self& *s1*);

reverse_iterator Specific

self // *returned value positioned at* base()-*n*
reverse_iterator::**operator+**(
Distance *n*) const;

self& // *change & return position to* base()-*n*
reverse_iterator::**operator+=**(Distance *n*);

self // *returned value positioned at* base()+*n*
reverse_iterator::**operator-**(
Distance *n*) const;

self& // *change & return position to* base()+*n*
reverse_iterator::**operator-=**(Distance *n*);

Reference // `*(*this + n)`
reverse_iterator::**operator[]**(Distance *n*);

Distance // *r0*.base() - *r1*.base()
operator-(const self& *r0*, const self& *r1*);

self // *n* + *r*.base()
operator-(Distance *n*, const self& *r*);

bool // *r0*.base() < *r1*.base()
operator<(const self& *r0*, const self& *r1*);

6.3.2 Insert Iterators

```
template⟨class Container⟩
class back_insert_iterator :
      public output_iterator;
```

```
template⟨class Container⟩
class front_insert_iterator :
      public output_iterator;
```

```
template⟨class Container⟩
class insert_iterator :
      public output_iterator;
```

Here T will denote the Container::value_type.

Constructors

explicit // ∃ Container::push_back(const T&)
back_insert_iterator::back_insert_iterator(
Container& *x*);

explicit // ∃ Container::push_front(const T&)
front_insert_iterator::front_insert_iterator(
Container& *x*);

// ∃ Container::insert(const T&)
insert_iterator::insert_iterator(
Container *x*,
Container::iterator *i*);

Denote
  InsIter = **back_insert_iterator**
  insFunc = **push_back**
  iterMaker = **back_inserter** ☞7.4
or
  InsIter = **front_insert_iterator**
  insFunc = **push_front**
  iterMaker = **front_inserter**
or
  InsIter = **insert_iterator**
  insFunc = **insert**

Member Functions & Operators

InsIter& // *calls* x.insFunc*(val)*
InsIter::**operator=**(const $\mathbb{T}$& *val*);

InsIter& // *return* `*this`
InsIter::**operator***();

InsIter& // *no-op, just* `return *this`
InsIter::**operator++**();

InsIter& // *no-op, just* `return *this`
InsIter::**operator++**(int);

Template Function

InsIter // *return* InsIter⟨$\mathbb{C}$ontainer⟩*(x)*
iterMaker($\mathbb{C}$ontainer& x);

// *return* insert_iterator⟨$\mathbb{C}$ontainer⟩(x, i)
insert_iterator⟨$\mathbb{C}$ontainer⟩
inserter($\mathbb{C}$ontainer& x, $\mathbb{I}$terator i);

7 Examples

7.1 Vector

```
// safe get
int  vi(const vector<unsigned>& v, int i)
{ return(i < (int)v.size() ? (int)v[i] : -1);}

// safe set
void vin(vector<int>& v, unsigned i, int n) {
   int  nAdd = i - v.size() + 1;
   if (nAdd>0) v.insert(v.end(), nAdd, n);
   else v[i] = n;
}
```

7.2 List Splice

```
void lShow(ostream& os, const list<int>& l) {
 ostream_iterator<int> osi(os, " ");
 copy(l.begin(), l.end(), osi); cout<<endl;}

void lmShow(ostream& os, const char* msg,
            const list<int>& l,
            const list<int>& m) {
 os << msg << (m.size() ? ":\n" : ": ");
 lShow(os, l);
 if (m.size()) lShow(os, m); } // lmShow

list<int>::iterator
p(list<int>& l, int val)
{ return find(l.begin(), l.end(), val);}

 static int prim[] = {2, 3, 5, 7};
 static int perf[] = {6, 28, 496};
 const list<int> lPrimes(prim+0, prim+4);
 const list<int> lPerfects(perf+0, perf+3);
 list<int> l(lPrimes), m(lPerfects);
 lmShow(cout, "primes & perfects", l, m);
 l.splice(l.begin(), m);
 lmShow(cout, "splice(l.beg, m)", l, m);
 l = lPrimes; m = lPerfects;
 l.splice(l.begin(), m, p(m, 28));
 lmShow(cout, "splice(l.beg, m, ^28)", l, m);
 m.erase(m.begin(), m.end()); // <=>m.clear()
 l = lPrimes;
 l.splice(p(l, 3), l, p(l, 5));
 lmShow(cout, "5 before 3", l, m);
 l = lPrimes;
 l.splice(l.begin(), l, p(l, 7), l.end());
 lmShow(cout, "tail to head", l, m);
 l = lPrimes;
 l.splice(l.end(), l, l.begin(), p(l, 3));
 lmShow(cout, "head to tail", l, m);
```

☞➠

```
primes & perfects:
2 3 5 7
6 28 496
splice(l.beg, m): 6 28 496 2 3 5 7
splice(l.beg, m, ^28):
28 2 3 5 7
6 496
5 before 3: 2 5 3 7
tail to head: 7 2 3 5
head to tail: 3 5 7 2
```

7.3 Compare Object Sort

```
class ModN {
 public:
  ModN(unsigned m): _m(m) {}
  bool operator ()(const unsigned& u0,
                   const unsigned& u1)
       {return ((u0 % _m) < (u1 % _m));}
 private: unsigned _m;
}; // ModN

 ostream_iterator<unsigned> oi(cout, " ");
 unsigned  q[6];
 for (int n=6, i=n-1;  i>=0;  n=i--)
    q[i] = n*n*n*n;
 cout<<"four-powers:   ";
 copy(q + 0, q + 6, oi);
 for (unsigned b=10; b<=1000; b *= 10) {
  vector<unsigned>  sq(q + 0, q + 6);
  sort(sq.begin(), sq.end(), ModN(b));
  cout<<endl<<"sort mod "<<setw(4)<<b<<": ";
  copy(sq.begin(), sq.end(), oi);
 } cout << endl;
```

☞➠

```
four-powers:   1 16 81 256 625 1296
sort mod   10: 1 81 625 16 256 1296
sort mod  100: 1 16 625 256 81 1296
sort mod 1000: 1 16 81 256 1296 625
```

7.4 Stream Iterators

```
void unitRoots(int n) {
 cout << "unit " << n << "-roots:" << endl;
 vector<complex<float> > roots;
 float  arg = 2.*M_PI/(float)n;
 complex<float> r, r1 = polar((float)1., arg);
 for (r = r1; --n;  r *= r1)
   roots.push_back(r);
 copy(roots.begin(), roots.end(),
      ostream_iterator<complex<float> >(cout,
                                        "\n"));
} // unitRoots

 {ofstream("primes.txt") << "2 3 5";}
 ifstream pream("primes.txt");
 vector<int> p;
 istream_iterator<int>  priter(pream);
 istream_iterator<int>  eosi;
 copy(priter, eosi, back_inserter(p));
 for_each(p.begin(), p.end(), unitRoots);
```

☞➠

```
unit 2-roots:
(-1.000,-0.000)
unit 3-roots:
(-0.500,0.866)
(-0.500,-0.866)
unit 5-roots:
(0.309,0.951)
(-0.809,0.588)
(-0.809,-0.588)
(0.309,-0.951)
```

7.5 Binary Search

```
 // first 5 Fibonacci
 static int fb5[] = {1, 1, 2, 3, 5};
 for (int n = 0; n <= 6; ++n) {
   pair<int*,int*> p =
      equal_range(fb5, fb5+5, n);
   cout<< n <<":["<< p.first-fb5 <<','
                  << p.second-fb5 <<"] ";
   if (n==3 || n==6) cout << endl;
 }
```

☞

```
0:[0,0] 1:[0,2] 2:[2,3] 3:[3,4]
4:[4,4] 5:[4,5] 6:[5,5]
```

7.6 Transform & Numeric

```
template <class T>
class AbsPwr : public unary_function<T, T> {
 public:
    AbsPwr(T p): _p(p) {}
    T operator()(const T& x) const
       { return pow(fabs(x), _p); }
 private: T _p;
}; // AbsPwr

float normNP(const float* xb,
             const float* xe,
             float p) {
  vector<float>  vf;
  transform(xb, xe, back_inserter(vf),
            AbsPwr<float>(p > 0. ? p : 1.));
  return( (p > 0.)
  ? pow(accumulate(vf.begin(), vf.end(), 0.),
        1./p)
  : *(max_element(vf.begin(), vf.end())));
} // normNP

float distNP(const float* x, const float* y,
             unsigned n, float p) {
  vector<float>  diff;
  transform(x, x + n, y, back_inserter(diff),
            minus<float>());
  return normNP(diff.begin(), diff.end(), p);
} // distNP

 float  x3y4[] = {3., 4.,  0.};
 float  z12[]  = {0., 0., 12.};
 float  p[] = {1., 2., M_PI, 0.};
 for (int i=0; i<4;  ++i) {
  float d = distNP(x3y4, z12, 3, p[i]);
  cout << "d_{" << p[i] << "}=" << d << endl;
 }
```

☞

```
d_{1}=19
d_{2}=13
d_{3.14159}=12.1676
d_{0}=12
```

7.7 Iterator and Binder

```
// self-refering int
class Interator : public
   input_iterator<int, size_t> {
  int  _n;
 public:
  Interator(int n=0) : _n(n) {}
  int operator*() const {return _n;}
  Interator& operator++() {
    ++_n;  return *this;  }
  Interator  operator++(int) {
    Interator t(*this);
    ++_n;   return t;}
}; // Interator
bool operator==(const Interator& i0,
                const Interator& i1)
{ return (*i0 == *i1); }

struct Fermat: public
    binary_function<int, int, bool> {
  Fermat(int p=2) : n(p) {}
  int n;
  int nPower(int t) const { // t^n
    int i=n, tn=1;
    while (i--) tn *= t;
    return tn; } // nPower
  int nRoot(int t) const {
    return (int)pow(t +.1, 1./n); }
  int xNyN(int x, int y) const   {
    return(nPower(x)+nPower(y)); }
  bool operator()(int x, int y) const {
    int zn = xNyN(x, y), z = nRoot(zn);
    return(zn == nPower(z));  }
}; // Fermat


 for (int n=2; n<=Mp; ++n) {
   Fermat fermat(n);
   for (int x=1; x<Mx; ++x) {
     binder1st<Fermat>
       fx = bind1st(fermat, x);
     Interator iy(x), iyEnd(My);
     while ((iy = find_if(++iy, iyEnd, fx))
            != iyEnd) {
       int  y = *iy,
         z = fermat.nRoot(fermat.xNyN(x, y));
       cout << x << '^' << n << " + "
            << y << '^' << n << " = "
            << z << '^' << n << endl;
       if (n>2)
         cout << "Fermat is wrong!" << endl;
     }
   }
 }
```

☞

```
3^2 + 4^2 = 5^2
5^2 + 12^2 = 13^2
6^2 + 8^2 = 10^2
7^2 + 24^2 = 25^2
```